



SHREDDER TECHNICAL SPECIFICATIONS

ST-35E

MEASUREMENTS

M/C Length	82"
M/C Width	64"
M/C Height	105"
M/C Weight	2, 820 lbs
Floor Space (sq.ft.)	37

PRODUCT SPECIFICATIONS

Drive	Electric
Number of Motors	2
Horsepower	30 & 25 (55) HP
Voltage	208-600
Hertz	60
Knife Thickness (STD)	1/2", 5/8"
Number of Knives	46, 52
Knife Diameter	9 1/2"
Hex Size	4"
Distance Between Shafts	8 1/4"
Cutting Chamber	21"x25"
Discharge Height	40
Hopper Height	44"
Stand Opening (width)	21"
Stand Opening (length)	40"

OPTIONAL FEATURES

- PLC Interfacing for Peripheral Equipment
- Custom Stands and Hoppers
- Feed and Discharge Conveyors
- Pneumatic or Hydraulic Ram
- Explosion Proof Motors
- Modem Capabilities
- Magnetic or Eddy Current Separators
- Hydraulic Drive Options

ST-35E

2 - SHAFT SHREDDER

The ST-35E's brilliant design results in amazing throughput and payload at an equally amazing price.

MAINTENANCE



Several design refinements proven successful to increase ease of maintenance and shredder durability in Shred-Tech's model line up have been incorporated into the ST-35 shredder. The new cast aluminum body design, in combination with bulkhead walls and labyrinth barriers at either end of the cutting chamber provide excellent bearing and seal protection.

A light weight chamber plate ensures cutting chamber disassembly is quick and easy. Bearing and seal replacement is easily completed without the need of gearbox disassembly.

COMPLETE INFORMATION DESTRUCTION AND RECYCLING SOLUTIONS

www.shred-tech.com | shred@shred-tech.com

tf. 1.800.465.3214 | t. 519.621.3560 | f. 519.621.4288

Service Hotline: 1.877.566.2345